

RIB IMPLEMENT (A) - Technische Daten



Description

RIB IMPLEMENT (A) wurde für Anhänger und landwirtschaftliche Geräte bei Transport und Bodenbearbeitung entwickelt. Er ist ideal für die moderne Landwirtschaft und glänzt mit hervorragenden Leistungen auf und abseits der Straße. RIB IMPLEMENT (A) ist die richtige Wahl für alle Einsatzbedingungen, die einen hohen Level an Manövrierbarkeit sowie reduzierte Bodenverdichtung zum Schutz Ihrer Kulturpflanzen benötigen.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TL
Tyre Size	10.0/80 - 12
LI/SS FREE ROLLING	110 A8

Dimensions US Standard

Usa code	94010868
Ply Rating	6
Section Width (inch)	10.4
Overall Diameter (inch)	29.4
Static Loaded Radius (inch)	13
Rolling Circumference (inch)	86.1
Rim Rec	9.00
Rim Alt	7.0
ECE	E11-106R-003533

Load capacity (lbs)

mph / psi	33
5 FR	3270
15 FR	2780
20 FR	2610
25 FR	2340

Printed on 06.05.2024 20:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..