

RIB IMPLEMENT (B) - Technische Daten



Description

RIB IMPLEMENT (B) wurde speziell für landwirtschaftliche Geräte entwickelt. Dieser für die Anforderungen moderner Landwirtschaft hervorragend geeignete Reifen wurde aus einer speziellen, gegen Stoppeln resistenten Gummimischung hergestellt, die ausgezeichnete Durchstoßfestigkeit bietet. RIB IMPLEMENT (B) ist ein Reifen mit 5-fachem Rippenprofil, der eine robuste Karkasse aufweist und so eine längere Lebensdauer gewährleistet. Die beste Wahl für alle Einsatzbedingungen, die hohe Tragfähigkeit neben geringem Rollwiderstand erfordern.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte

Version	STANDARD
Type	TT
Tyre Size	49 - 17
LI/SS DRIVE WHEEL	146 A8/143 B
LI/SS FREE ROLLING	158 A8/154 B

Dimensions US Standard

Usa code	94046591
Ply Rating	20
Section Width (inch)	16.7
Overall Diameter (inch)	47.2
Rim Rec	13.0
Rim Alt	14.0
ECE	E11-106R-004653

Load capacity (lbs)

mph / psi	58
25 FR	9370
30 FR	8270
25 DW	6610
30 DW	6000

Printed on 19.04.2024 19:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..