

## RIDEMAX FL 615 - Datenblatt



### Description

RIDEMAX FL 615 ist ein radialer Flotationsreifen, der für frei rollende Anwendungen mit Tankwagen und Streumaschinen geeignet ist. Die Stahlgürtelstruktur bietet eine hohe Durchstichfestigkeit sowie erhöhte Haltbarkeit und ausgezeichnete Tragfähigkeit. RIDEMAX FL 615 sorgt für geringen Rollwiderstand auf der Straße mit hervorragenden Selbstreinigungseigenschaften auf dem Feld. Das abgerundete Schulterdesign und die breite Aufstandsfläche sorgen für beste Bodenschonung.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Streumaschine • Tankwagen • Anhänger

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>800/65 R 32</b>	STEEL BELTED	185 D	185 D	185 D	DW 27 B		830	1853	834	5624	875	TL	E11-106R-007528
<b>VF800/65 R 32</b>	STEEL BELTED	190 D	190 D	190 D	DW 28 B		815	1850	811	5610	875	TL	E11-106R-0010408

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23.04.2025 17:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..