

## RIDEMAX FL 690 - Technische Daten



### Description

RIDEMAX FL 690 ist ein radialer Flotations- und Transportreifen für Tankwagen und Anhänger. Der Reifen eignet sich für Anwendungen mit 75% Straßenfahrten. Als Antwort auf den wachsenden Bedarf immer schwererer Lasten in der modernen Landwirtschaft, entwarf BKT diesen Reifen mit Stahlgürteln, der auch besonders schweren Lasten standhält. Dies steigert die Produktivität der Landwirte. Außerdem trägt der geringe Rollwiderstand zur Kraftstoffersparnis bei.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Tankwagen • Anhänger  
Industrie: Anhänger

|           |                                |
|-----------|--------------------------------|
| Version   | STANDARD                       |
| Type      | TL                             |
| Tyre Size | VF 900/65 R 32<br>(VF35.5LR32) |
| LI/SS     | 197 D                          |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 930             |
| Overall Diameter (mm)      | 1986            |
| Static Loaded Radius (mm)  | 838             |
| Rolling Circumference (mm) | 5878            |
| SRI (mm)                   | 925             |
| Rim Rec                    | DW 31 B         |
| Rim Alt                    | DW 30 ; TW 30   |
| ECE                        | E11-106R-006917 |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.2   | 1.6   | 2.0   | 2.4   | 2.8   |
|------------|------|-------|-------|-------|-------|-------|
| 70         | 5030 | 6435  | 7840  | 8890  | 10295 | 11695 |
| 65         | 5530 | 7070  | 8610  | 9770  | 11310 | 12850 |
| 50         | 6470 | 8270  | 10075 | 11430 | 13235 | 15035 |
| 40         | 7130 | 9120  | 11110 | 12605 | 14595 | 16580 |
| 10         | 9065 | 11595 | 14125 | 16020 | 18550 | 21075 |

Printed on 28.04.2024 04:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..