

RIDEMAX FL 693 M - Technische Daten



Description

RIDEMAX FL 693 M ist der ideale Reifen für all diejenigen, die oft Straßenabschnitte mit Anhängern/Tankwagen befahren. Für 70% Straßeneinsatz entwickelt zeichnet sich RIDEMAX FL 693 M durch vortreffliche Leistungen auf der Straße aus. Hierbei stehen Eigenschaften wie Komfort und Selbstreinigung im Vordergrund. Der Geschwindigkeitsindex Klasse D/E der Serie ist ein Synonym für höhere Geschwindigkeiten auf Straßenfahrten bei gleichzeitig deutlicher Zeitersparnis. Der geringe Rollwiderstand trägt zur Kraftstoffersparnis bei, während der verstärkte Wulst größere Beständigkeit gewährleistet.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Tankwagen • Anhänger

| | |
|-----------|---------------|
| Version | HD |
| Type | TL |
| Tyre Size | 650/55 R 26.5 |
| LI/SS | 178 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94049622 |
| Section Width (inch) | 25.4 |
| Overall Diameter (inch) | 54.7 |
| Static Loaded Radius (inch) | 24.2 |
| Rolling Circumference (inch) | 167.3 |
| Rim Rec | AG 20.00 |
| ECE | E11-106R-003008 |

Load capacity (lbs)

| mph / psi | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 73 | 87 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 5130 | 6120 | 7440 | 8600 | 9920 | 11240 | 12070 | 13390 | 14720 | 15540 | 16530 |
| 30 | 6210 | 7410 | 9010 | 10410 | 12000 | 13610 | 14600 | 16210 | 17810 | 18820 | 20010 |
| 25 | 6980 | 8320 | 10120 | 11690 | 13490 | 15300 | 16420 | 18220 | 20020 | 21140 | 22490 |
| 20 | 7750 | 9250 | 11240 | 12980 | 14980 | 16990 | 18230 | 20230 | 22220 | 23480 | 24970 |
| 15 | 8100 | 9670 | 11760 | 13590 | 15670 | 17770 | 19080 | 21160 | 23260 | 24560 | 26120 |
| 5 | 9230 | 11010 | 13390 | 15480 | 17860 | 20240 | 21730 | 24110 | 26490 | 27980 | 29760 |

Printed on 24.04.2024 05:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..