

## RIDEMAX IT 696 - Technische Daten



### Description

Das spezielle Laufflächendesign mit breiter Aufstandsfläche von RIDEMAX IT 696 verleiht ausgezeichnete Haftung beim Straßeneinsatz auch in winterlichen Bedingungen. Der Reifen eignet sich nicht zuletzt wegen seiner hohen Geschwindigkeiten und der robusten Karkasse besonders für Anwendungen im Bereich Transport und Gemeindearbeiten/Wartung. Das Laufflächendesign wurde speziell zum Schwersteinsatz entworfen und gewährleistet geringen Rollwiderstand, der sich in Kraftstoffersparnis und großer Stabilität zeigt.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Traktor

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 360/80 R 20 IND |
| LI/SS     | 143D/147A8      |

## Dimensions US Standard

|                              |                         |
|------------------------------|-------------------------|
| Usa code                     | 94071074                |
| Section Width (inch)         | 14.1                    |
| Overall Diameter (inch)      | 42.7                    |
| Static Loaded Radius (inch)  | 19.2                    |
| Rolling Circumference (inch) | 127.4                   |
| Rim Rec                      | 11                      |
| Rim Alt                      | W 10 ; W 11 ; 12 ; W 12 |
| ECE                          | E11-106R-007845         |

## Load capacity (lbs)

| mph / psi | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   |
|-----------|------|------|------|------|------|------|------|------|
| 40        | 2890 | 3490 | 4160 | 4630 | 4810 | 4990 | 5470 | 6010 |
| 30        | 3120 | 3770 | 4490 | 5000 | 5200 | 5390 | 5910 | 6490 |
| 25        | 3260 | 3940 | 4680 | 5220 | 5420 | 5630 | 6170 | 6780 |
| 20        | 3460 | 4190 | 4980 | 5560 | 5780 | 5990 | 6570 | 7210 |

Printed on 23.04.2024 09:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..