

## RIDEMAX IT 696 - Datenblatt



### Description

Das spezielle Laufflächendesign mit breiter Aufstandsfläche von RIDEMAX IT 696 verleiht ausgezeichnete Haftung beim Straßeneinsatz auch in winterlichen Bedingungen. Der Reifen eignet sich nicht zuletzt wegen seiner hohen Geschwindigkeiten und der robusten Karkasse besonders für Anwendungen im Bereich Transport und Gemeindearbeiten/Wartung. Das Laufflächendesign wurde speziell zum Schwersteinsatz entworfen und gewährleistet geringen Rollwiderstand, der sich in Kraftstoffersparnis und großer Stabilität zeigt.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Traktor

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
<b>240/70 R 16 IND</b>	STANDARD	107A8/107B	W8	W9	244	742	343	2226	350	TL		E11-106R-006942
<b>340/80 R 18 IND</b>	STANDARD	143 A8/138 D	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	343	1001	458	2980	475	TL		E11-106R-002987
<b>360/80 R 20 IND</b>	STANDARD	143D/147A8	11	W 10 ; W 11 ; 12 ; W 12	357	1084	488	3235	525	TL		E11-106R-007845
<b>300/80 R 24 IND (11.2 R 24)</b>	STANDARD	133 A8/128 D	DW 10		295	1090	501	3296	525	TL		E4-106R-002292
<b>340/80 R 24 IND (12.4 R 24)</b>	STANDARD	140 A8/135 D	DW 11	W 10 ; W 12 ; DW 10	343	1154	521	3444	550	TL		E4-106R-002293
<b>360/80 R 24 IND (13.6 R 24)</b>	STANDARD	143 A8/138 D	DW 11	W 12 ; W 10	343	1186	537	3556	575	TL		E11-106R-004753
<b>400/80 R 24 IND (14.9 R 24)</b>	STANDARD	149 A8/144 D	DW 13	W 12 ; W 14 L	404	1250	558	3760	600	TL		E4-106R-002400
<b>420/65 R 24 IND</b>	STANDARD	146 D/151 A8	DW 13 L ; W13	DW 15 L ; DW 14 L	418	1158	530	3483	550	TL	1	E11-106R-005952
<b>440/80 R 24 IND (16.9 R 24)</b>	STANDARD	154 A8/149 D	DW 14 L	DW 15 L ; DW 13	441	1314	590	3939	625	TL		E11-106R-004760
<b>460/65 R 24 IND</b>	STANDARD	151 D/156 A8	DW 14 L	DW 15 L ; DW 13	455	1214	549	3644	600	TL	1	
<b>500/70 R 24 IND</b>	STANDARD	164A8/159D	DW 16 L	DW 15 L ; DW 18 L	503	1310	602	3954	625	TL		E11-106R-007547
<b>500/70 R 24 IND</b>	STANDARD	157 A8/152 D	DW 16 L	DW 15 L ; DW 18 L	503	1310	602	3954	625	TL		E11-106R-007051
<b>400/80 R 28 IND (14.9 R 28)</b>	STANDARD	151 A8/146 D	W 13	W 12 ; W 14 L	404	1352	615	4048	650	TL		E4-106R-002401
<b>440/80 R 28 IND (16.9 R 28)</b>	STANDARD	156 A8/151 D	W 14 L	W 15 L	441	1415	634	4288	675	TL		E4-106R-002299
<b>440/80 R 30 IND (16.9 R 30)</b>	STANDARD	157 A8/153 D	W 14 L	W 15 L	441	1466	668	4456	700	TL		E4-106R-002297
<b>480/80 R 30 IND (18.4 R 30)</b>	STANDARD	162 A8/157 D	W 15 L	W 16 L	479	1530	673	4558	725	TL		E4-106R-002298
<b>440/80 R 34 IND (16.9 R 34)</b>	STANDARD	159 A8/155 D	DW 14 L	DW 15 L ; DW 16 L	441	1567	704	4775	750	TL		E4-106R-002295
<b>480/80 R 34 IND (18.4 R 34)</b>	STANDARD	164 A8/159 D	W 15 L	W 16 L	479	1632	728	4894	775	TL		E4-106R-002296
<b>480/80 R 38 IND (18.4 R 38)</b>	STANDARD	166 A8/161 D	W 15 L	W 16 L	479	1733	780	5213	825	TL		E11-106R-004075
<b>540/80 R 38 IND</b>	STANDARD	172 A8/167 D	W 18 L	W 16 L	550	1829	833	5537	875	TL		E11-106R-004077
<b>540/80 R 42 IND</b>	STANDARD	168 D/173 A8	W 18 L	W 16 L	560	1931	879	5875	925	TL		E11-106R-005714

Printed on 23.04.2024 15:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The

user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..