RIDEMAX IT 697 (M+S) - Technische Daten

Description

RIDEMAX IT 697 M+S ist die perfekte Antwort auf die Erwartungen und Anforderungen des modernen Lohnunternehmers in der Landwirtschaft bei winterlichen Arbeiten. Er eignet sich hervorragend für Transport- und Gemeindeanwendungen. Dieser Winterreifen für Traktoren bietet perfekte Haftung bei allen Arbeiten auf winterlichem Gelände mit Schnee und Eis, wobei sich die Montage von Schneeketten erübrigt. Dank der Einkerbungen der Lauffläche und der robusten Karkasse kann ein Traktor mit voller Stabilität auch bei hohen Geschwindigkeiten gefahren werden. Das Laufflächenprofil wurde speziell zum Schwersteinsatz entworfen und gewährleistet geringen Rollwiderstand, der sich in Kraftstoffersparnis und großer Stabilität zeigt.

UM

International Standard

Construction

RADIAL

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TL
Tyre Size	480/65 R 28 IND
LI/SS	149 D/154 A8

Dimensions International Standard

Section Width (mm)	480
Overall Diameter (mm)	1335
Static Loaded Radius (mm)	615
Rolling Circumference (mm)	4088
SRI (mm)	650
Rim Rec	DW 15 L
Rim Alt	DW 14 L ; DW 16 L
ECE	E11-106R-006159

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1530	1885	2210	2570	2895	3250
50	1650	2035	2385	2775	3125	3510
40	1765	2175	2550	2965	3340	3750
30	1835	2260	2650	3080	3470	3900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.10.2024 06:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..