RIDEMAX IT 697 (M+S) - Technische Daten

Description

RIDEMAX IT 697 M+S ist die perfekte Antwort auf die Erwartungen und Anforderungen des modernen Lohnunternehmers in der Landwirtschaft bei winterlichen Arbeiten. Er eignet sich hervorragend für Transport- und Gemeindeanwendungen. Dieser Winterreifen für Traktoren bietet perfekte Haftung bei allen Arbeiten auf winterlichem Gelände mit Schnee und Eis, wobei sich die Montage von Schneeketten erübrigt. Dank der Einkerbungen der Lauffläche und der robusten Karkasse kann ein Traktor mit voller Stabilität auch bei hohen Geschwindigkeiten gefahren werden. Das Laufflächenprofil wurde speziell zum Schwersteinsatz entworfen und gewährleistet geringen Rollwiderstand, der sich in Kraftstoffersparnis und großer Stabilität zeigt.

UM

US Standard

Construction

RADIAL

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TL
Tyre Size	540/65 R 30 IND
LI/SS	156 D/161 A8

Dimensions US Standard

Usa code	94048106
Section Width (inch)	20.9
Overall Diameter (inch)	57.6
Static Loaded Radius (inch)	26.5
Rolling Circumference (inch)	175
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E11-106R-003015

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	4140	5110	6000	6970	7850	8820
30	4480	5520	6480	7530	8480	9520
25	4790	5920	6930	8060	9070	10200
20	4970	6140	7200	8360	9410	10580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.10.2024 06:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..