RIDEMAX IT 697 (M+S) - Technische Daten

Description

RIDEMAX IT 697 M+S ist die perfekte Antwort auf die Erwartungen und Anforderungen des modernen Lohnunternehmers in der Landwirtschaft bei winterlichen Arbeiten. Er eignet sich hervorragend für Transport- und Gemeindeanwendungen. Dieser Winterreifen für Traktoren bietet perfekte Haftung bei allen Arbeiten auf winterlichem Gelände mit Schnee und Eis, wobei sich die Montage von Schneeketten erübrigt. Dank der Einkerbungen der Lauffläche und der robusten Karkasse kann ein Traktor mit voller Stabilität auch bei hohen Geschwindigkeiten gefahren werden. Das Laufflächenprofil wurde speziell zum Schwersteinsatz entworfen und gewährleistet geringen Rollwiderstand, der sich in Kraftstoffersparnis und großer Stabilität zeigt.

UM

International Standard

Construction

RADIAL

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TL
Tyre Size	650/85 R 38 IND
LI/SS	178 D/ 183 A8

Dimensions International Standard

Section Width (mm)	709
Overall Diameter (mm)	2071
Static Loaded Radius (mm)	974
Rolling Circumference (mm)	6280
SRI (mm)	975
Rim Rec	DW 23 B
Rim Alt	DW 20 B ; DW 21 B
ECE	E11-106R-006761

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	3525	4350	5100	5925	6675	7500
50	3805	4700	5510	6400	7210	8100
40	4115	5075	5950	6915	7790	8750
30	4230	5220	6120	7110	8010	9000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.10.2024 05:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..