

## RIDEMAX IT 697 (M+S) - Technische Daten



### Description

RIDEMAX IT 697 M+S ist die perfekte Antwort auf die Erwartungen und Anforderungen des modernen Lohnunternehmers in der Landwirtschaft bei winterlichen Arbeiten. Er eignet sich hervorragend für Transport- und Gemeindeganwendungen. Dieser Winterreifen für Traktoren bietet perfekte Haftung bei allen Arbeiten auf winterlichem Gelände mit Schnee und Eis, wobei sich die Montage von Schneeketten erübrigt. Dank der Einkerbungen der Lauffläche und der robusten Karkasse kann ein Traktor mit voller Stabilität auch bei hohen Geschwindigkeiten gefahren werden. Das Laufflächenprofil wurde speziell zum Schwersteinsatz entworfen und gewährleistet geringen Rollwiderstand, der sich in Kraftstoffersparnis und großer Stabilität zeigt.

### UM

International Standard

### Construction

RADIAL

### Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 42
LI/SS	180 D/185 A8

### Dimensions International Standard

TKPH	1
Section Width (mm)	716
Overall Diameter (mm)	2068
Static Loaded Radius (mm)	926
Rolling Circumference (mm)	6264
Rim Rec	DW23 B

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	3760	4640	5440	6320	7120	8000
50	4060	5010	5875	6825	7690	8640
40	4350	5365	6290	7310	8235	9250
30	4510	5570	6530	7585	8545	9600

Printed on 21.10.2020 06:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..