

RM 2002 - Technische Daten



Description

RM 2002 eignet sich für Transportarbeiten mit Anhängern und Leicht-LKWs auf und abseits der Straße. Er gewährleistet lange Beständigkeit und hervorragende Leistung während des gesamten Produktlebenszyklus. Die Ausführung "industrial" ist ideal für Pick & Carry Kräne.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Anhänger
Industrie: Mobilkran

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

Dimensions US Standard

Usa code	94022656
Ply Rating	16
Section Width (inch)	11.9
Overall Diameter (inch)	43.3
Rim Rec	8.0
Rim Alt	7.5 ; 8.5

Load capacity (lbs)

mph / psi	115	105
62 LS	7165	-
62 LD	-	6395

Printed on 25.04.2024 19:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..