

## RM 2002 - Datenblatt



### Description

RM 2002 eignet sich für Transportarbeiten mit Anhängern und Leicht-LKWs auf und abseits der Straße. Er gewährleistet lange Beständigkeit und hervorragende Leistung während des gesamten Produktlebenszyklus. Die Ausführung "industrial" ist ideal für Pick & Carry Kräne.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Landwirtschaft: Anhänger  
Industrie: Mobilkran

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
11.00 - 20	INDUSTRIAL	18	8.0	7.5 ; 8.5	302	1101	0	0	TT
11.00 - 20	INDUSTRIAL	16	8.0	7.5 ; 8.5	302	1101	0	0	TT
11.00 - 20	STANDARD	16	8.0	7.5 ; 8.5	302	1101	0	0	TT
11.00 - 20	STANDARD	18	8.0	7.5 ; 8.5	302	1101			TT
12.00 - 20	STANDARD	18	8.5	8.0 ; 9.0	315	1145	534	3538	TT

Printed on 25.04.2024 18:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..