

ROCK GRIP E4 - Technische Daten



Description

ROCK GRIP (E-4) ist ein Diagonalreifen, der speziell zum Einsatz mit Lastfahrzeugen bei Minenarbeiten oder in Steinbrüchen zum Einsatz kommt. Wann immer Ihre Betriebsbedingungen für kurze Fahrten am Standort sowohl Hitzebeständigkeit als auch Schnittfestigkeit erfordern, ist ROCK GRIP der richtige Reifen, auf den Sie zählen können.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Starrer Muldenkipper

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	32
Section Width (mm)	510
Overall Diameter (mm)	1650
Static Loaded Radius (mm)	753
Rolling Circumference (mm)	4885
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.75	7.50
50	8750	-
10	-	15000

Printed on 25.04.2024 08:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..