

ROCK GRIP IND4 (ECH) - Technische Daten



Description

Der ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) ist ein Diagonalreifen, der für den Leercontainerumschlag in verschiedenen Anwendungsbereichen entwickelt wurde, u. a. in der Industrie und in Stahlwerken. Die spezielle ROCK GRIP-Mischung sorgt für besondere Hitzebeständigkeit bei gleichzeitig hoher Stabilität und Haltbarkeit.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Leercontainerstapler

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

Dimensions US Standard

Usa code	94052059
Ply Rating	32
Overall Width (inch)	18.5
Overall Diameter (inch)	60
Static Loaded Radius (inch)	27.5
Rolling Circumference (inch)	177.7
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	37200

Printed on 25.04.2024 22:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..