

## ROCK GRIP L4 - Technische Daten



### Description

ROCK GRIP (L-4) ist ein Diagonalreifen entworfen für Radladerarbeiten unter härtesten Einsatzbedingungen auf unwegsamem Gelände. Die speziell entworfene, schnitt- und reißfeste Gummimischung der Lauffläche reduziert Reifenpannen und somit die Stillstandzeiten. Die Lauffläche mit Tiefe (L-4) verleiht einen verlängerten Reifenlebenszyklus.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Planierer • Radlader

Version	STANDARD
Type	TL
Tyre Size	14.00 - 25

## Dimensions International Standard

Ply Rating	24
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4173
Rim Rec	10.00/1.5
TRA Code	L4

## Load capacity (Kg)

km/h / bar	8.50
10	9500

Printed on 18.04.2024 23:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..