

ROCK GRIP L4 - Datenblatt



Description

ROCK GRIP (L-4) ist ein Diagonalreifen entworfen für Radladerarbeiten unter härtesten Einsatzbedingungen auf unwegsamem Gelände. Die speziell entworfene, schnitt- und reißfeste Gummimischung der Lauffläche reduziert Reifenpannen und somit die Stillstandzeiten. Die Lauffläche mit Tiefe (L-4) verleiht einen verlängerten Reifenlebenszyklus.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Planierer • Radlader

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	L4	24	10.00/1.5		375	1410	649	4173	TT
14.00 - 25	STANDARD	L4	24	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	L4	28	10.00/1.5		375	1410	649	4173	TT
14.00 - 25	STANDARD	L4	28	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	L4	32	10.00/1.5		375	1410	649	4173	TL

Printed on 19.04.2024 02:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..