

ROCK GRIP (T) - Datenblatt



Description

ROCK GRIP (E-4) eignet sich bestens für Kipper in Steinbrüchen und für kurze Strecken im Bergbau zur Beförderung schwerer Lasten. Die spezielle Gummimischung der Lauffläche reduziert Schnitte und Durchstöße auf härtesten Bodenbedingungen. ROCK GRIP (E-4) bietet erstklassige Traktion und einen verlängerten Reifenlebenszyklus.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Kipper • Starrer Muldenkipper

| SIZE | Version | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|------------|----------|----|---------|---------|-----|------|-----|------|------|
| 10.00 - 20 | STANDARD | 18 | 7.5 | 7.0 | 280 | 1090 | 0 | 0 | TT |
| 11.00 - 20 | STANDARD | 18 | 8.0 | 7.5 | 300 | 1135 | 0 | 0 | TT |
| 12.00 - 20 | STANDARD | 20 | 8.5 | 8.0 | 315 | 1172 | 0 | 0 | TT |
| 12.00 - 24 | STANDARD | 18 | 8.5 | 8.0 | 315 | 1265 | 595 | 3755 | TT |
| 12.00 - 24 | STANDARD | 20 | 8.5 | 8.0 | 315 | 1265 | 595 | 3755 | TT |

Printed on 25.04.2024 03:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..