

ROCK STAR (SB SPL) - Technische Daten



Description

ROCK STAR wurde speziell für Transportmittel zum Einsatz auf der Straße und auf Stahlschienen entworfen. ROCK STAR ist ein 32-lagiger Reifen, der hervorragende Tragfähigkeit bietet. Die einzigartige Gummimischung der Lauffläche bietet Schnitt- und Durchstoßfestigkeit, während die Stahlbänder eine lange Lebensdauer gewährleisten.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Zweiwegemaschinen

Version	STEEL BELTED SPL
Type	TL
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94057177
Ply Rating	32
Overall Width (inch)	15.4
Overall Diameter (inch)	56.1
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	31250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07.12.2024 18:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..