



RT 853 - Datenblatt



Description

RT 853 ist ein R-1 Reifen für Traktoren und Erntemaschinen am Weinberg zur Bodenbearbeitung und Anwendungen bei der Weinlese. Er bietet erstklassige Traktion und Tragfähigkeit sowie ausgezeichnete Selbstreinigungseigenschaften.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Traktor • Traubenerntemaschine

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
480/80 R 38 (18.4 R 38)	STANDARD	94045709	R1	149 A8/B	W 16 L	W 15 L ; W 14 L	18.7	68.8	31.2	208.7	TL	E4-106R-001822
520/85 R 38 (20.8 R 38)	STANDARD	94044771	R1	155 A8/B	DW 16 L	DW 18 L ; DD 16 L	20.3	72.8	32.7	220.2	TL	E4-106R-001483

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.01.2025 21:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..