

SAND KING - Technische Daten



Description

SAND KING ist ein Reifen mit Blockprofil, der speziell für Anhänger in Transportanwendungen entworfen wurde. Er verleiht ausgezeichnete Traktion und besten Bodenkontakt auf sandigem Gelände.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Anhänger

Version	STANDARD
Type	TT
Tyre Size	425 / 90 D - 21 (15.00 - 21)

Dimensions US Standard

Usa code	94068814
Ply Rating	18
Section Width (inch)	16.5
Overall Diameter (inch)	52.4
Rim Rec	11.25

Load capacity (lbs)

	mph / psi	95
	40	10900

Printed on 27.04.2024 10:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..