

SAND KING - Technische Daten



Description

SAND KING ist ein Reifen mit Blockprofil, der speziell für Anhänger in Transportanwendungen entworfen wurde. Er verleiht ausgezeichnete Traktion und besten Bodenkontakt auf sandigem Gelände.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Anhänger

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	10
Section Width (mm)	215
Overall Diameter (mm)	820
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2471
Rim Rec	5.50 F SDC
Rim Alt	6.00 G
ECE	E11-106R-005309

Load capacity (Kg)

km/h / bar	5.20
65 LS	1215

Printed on 27.04.2024 04:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..