

## SAND MASTER - Technische Daten



### Description

SAND MASTER ist ein Reifen mit Blockprofil, der speziell für Anhänger entworfen wurde. Er verleiht ausgezeichnete Traktion und besten Bodenkontakt auf sandigem Gelände.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Anhänger

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	215
<b>Overall Diameter (mm)</b>	820
<b>Rim Rec</b>	5.50 F SDC
<b>Rim Alt</b>	6.00 G

## Load capacity (Kg)

	km/h / bar	7.60
	65 LS	1550

Printed on 26.04.2024 06:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..