

## SAND STAR - Technische Daten



### Description

SAND STAR ist ein Reifen mit Blockprofil, der speziell für Anhänger entworfen wurde. Er verleiht ausgezeichnete Traktion und besten Bodenkontakt auf sandigem Gelände. Darüber hinaus reduziert er auch die Bodenverdichtung.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrie: Anhänger

Version	STANDARD
Type	TT
Tyre Size	9.00 - 13
LI/SS	116 A8

## Dimensions US Standard

Usa code	94031740
Ply Rating	8
Section Width (inch)	9.6
Overall Diameter (inch)	30.9
Rim Rec	5.50 F
Rim Alt	5.50 WB
ECE	E11-106R-005261

## Load capacity (lbs)

mph / psi	40
25 FR LLV	2760

Printed on 26.04.2024 23:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..