

SIERRA MAX - Technische Daten



Description

SIERRA MAX ist der BKT-Reifen für Geländefahrten und Gartenanwendungen. Die Radialkonstruktion verleiht einen besonders angenehmen Fahrkomfort auch auf extremem Gelände wie Wüste, Erdreich und steinigem Böden. Das spezielle Laufflächenprofil und die breitere Aufstandsfläche bieten hervorragende Vorwärts- und Seitentraktion.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Geländefahrzeug

Version	STANDARD
Type	TL
Tyre Size	AT 25 X 10 R 12
LI/SS	50 N

Dimensions US Standard

Usa code	94064793
Section Width (inch)	10.2
Overall Diameter (inch)	25.2
Static Loaded Radius (inch)	11.6
Rolling Circumference (inch)	75.7
Rim Rec	8.0
Star Rating	***
ECE	E11-75R-005087

Load capacity (lbs)

mph / psi	7
87	420

Printed on 23.04.2024 18:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..