

SIERRA MAX - Datenblatt



Description

SIERRA MAX ist der BKT-Reifen für Geländefahrten und Gartenanwendungen. Die Radialkonstruktion verleiht einen besonders angenehmen Fahrkomfort auch auf extremem Gelände wie Wüste, Erdreich und steinigen Böden. Das spezielle Laufflächenprofil und die breitere Aufstandsfläche bieten hervorragende Vorwärts- und Seitentraktion.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Geländefahrzeug

SIZE	Version	Star R	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
AT 25 X 10 R 12	STANDARD	***	50 N	8.0		260	640	294	1923	TL	E11-75R-005087
AT 25 X 8 R 12	STANDARD	***	43 N	6.5		206	640	292	1899	TL	E11-75R-005088
AT 26 X 11 R 14	STANDARD	***	54 N	9.00		280	675	310	2027	TL	E11-75R-005096
AT 26 X 9 R 14	STANDARD	***	48 N	7.00		230	675	307	2005	TL	E11-75R-005095
AT 27 X 11 R 14	STANDARD	***	56 N	9.00		280	700	318	2091	TL	E11-75R-005097
AT 27 X 9 R 14	STANDARD	***	50 N	7.00		230	700	316	2070	TL	E11-75R-005099

Printed on 23.04.2024 18:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..