

## SKID POWER ( CHEVRON ) - Technische Daten



### Description

SKID POWER (CHEVRON) wurde speziell für Skid-Steer-Lader bei Anwendungen im Baugewerbe entworfen. Er zeichnet sich durch ausgezeichnete Traktion sowie verbesserte Selbstreinigungseigenschaften aus. SKID POWER (CHEVRON) eignet sich besonders für lockeren Untergrund und bietet hohe Schnitt- und Reißfestigkeit.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Skid-Steer-Lader

Version	IMPLEMENT
Type	TL
Tyre Size	7.00 - 15
LI/SS	106 A8

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	203
Overall Diameter (mm)	762
Static Loaded Radius (mm)	347
Rolling Circumference (mm)	2295
Rim Rec	5.50 F
Rim Alt	6 LB
ECE	E11-106R-003583

## Load capacity (Kg)

km/h / bar	4.10
40	950

Printed on 27.04.2024 09:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..