

SKID POWER HD (A) - Technische Daten



Description

SKID POWER HD (A) wurde speziell für Skid-Steer-Lader bei Anwendungen im Baugewerbe entworfen. Der Reifen zeichnet sich durch eine extra tiefe Lauffläche und Flankenschutz aus, die ausgezeichnete Schnitt- und Reißfestigkeit sowie erstklassige Beständigkeit bieten. SKID POWER HD (A) ist der ideale Reifen auf lockerem Untergrund bei schweren Betriebsbedingungen.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Skid-Steer-Lader

Version	IMPLEMENT
Type	TL
Tyre Size	14 - 17.5
LI/SS	140 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	350
Overall Diameter (mm)	930
Static Loaded Radius (mm)	420
Rolling Circumference (mm)	2744
Rim Rec	10.50

Load capacity (Kg)

km/h / bar	5.50
40	2500

Printed on 24.04.2024 08:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..