

## SKID POWER - Technische Daten



### Description

SKID POWER wurde für Skid-Steer-Lader bei Anwendungen im Baugewerbe entworfen. Er bietet ausgezeichnete Traktion und zeichnet sich durch verbesserte Selbstreinigung aus. Der Reifen glänzt mit einer extra tiefen Lauffläche und zusätzlichem Flankenschutz, die ausgezeichnete Schnitt- und Reißfestigkeit sowie erstklassige Beständigkeit verleihen. SKID POWER ist der ideale Reifen auf lockerem Untergrund.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Skid-Steer-Lader

Version	IMPLEMENT
Type	TL
Tyre Size	10 - 16.5
LI/SS	116 A8

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	254
Overall Diameter (mm)	775
Static Loaded Radius (mm)	355
Rolling Circumference (mm)	2286
Rim Rec	8.25
ECE	E11-106R-003534

## Load capacity (Kg)

km/h / bar	4.10
40	1250

Printed on 25.04.2024 17:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..