

## SL 441 - Technische Daten



### Description

SL 441 wurde speziell zur Bodenbearbeitung und Transportanwendungen mit Anhängern und landwirtschaftlichen Geräten entwickelt. SL 441 wurde entworfen, um hervorragende Tragfähigkeit und ein langes Reifenleben zu bieten.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	113 A8

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	210
<b>Overall Diameter (mm)</b>	610
<b>Static Loaded Radius (mm)</b>	278
<b>Rolling Circumference (mm)</b>	1785
<b>Rim Rec</b>	AG 6.75
<b>ECE</b>	E11-106R-003610

## Load capacity (Kg)

	km/h / bar	7.00
	10 FR	1610
	25 FR	1370
	30 FR	1290
	40 FR	1150

Printed on 17.04.2024 05:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..