

SM 53 - Datenblatt



Description

SM 53 wurde speziell für Anwendungen im Untertagebau mit Ladearbeiten konzipiert. Der Reifen zeichnet sich durch hohe Stabilität sowie eine solide und hervorragend schnittfeste Lauffläche aus.

UM

International Standard

Construction

❖ BIAS

Machinery

OTR: Untertagefahrzeug

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
9.00 - 20	STANDARD	L3S	16	7.0		266	1040	472	3080	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 20.09.2024 02:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..