

## SM 54 L4S - Technische Daten



### Description

SM 54 (L-4S) wurde speziell für Leercontainerabfertiger und Reachstacker in intermodalen/logistischen Anwendungen entwickelt. Er zeichnet sich durch eine hohe Stabilität im Hebebetrieb sowie ein tiefes und glattes Profildesign aus, das eine ausgezeichnete Schnittfestigkeit bietet, um eine verlängerte Reifenlebensdauer zu gewährleisten.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrie: Reach-Stacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

## Dimensions US Standard

Usa code	94050208
Ply Rating	36
Overall Width (inch)	21.1
Overall Diameter (inch)	74.6
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	220.8
Rim Rec	13.00/2.5
TRA Code	L4S

## Load capacity (lbs)

mph / psi	145
5	55100

Printed on 02.12.2023 12:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..