

## SM 54 M IND-4S - Technische Daten



### Description

SM 54 M IND-4S ist eine modifizierte Version des SM 54 Modells. Das flachere Reifenprofil führt zu einer breiteren Aufstandsfläche und somit einem verlängerten Produktlebenszyklus. Der Reifen wurde speziell für Leercontainerstapler und Reachstacker in intermodalen und Logistikanwendungen entwickelt. SM 54 M wartet mit hoher Stabilität im Hebemodus auf und besitzt ein tiefes und glattes Laufflächenmuster, das ausgezeichnete Schnittfestigkeit bietet.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Reach-Stacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

## Dimensions International Standard

Ply Rating	40
Overall Width (mm)	535
Overall Diameter (mm)	1895
Static Loaded Radius (mm)	840
Rolling Circumference (mm)	5609
Rim Rec	13.00/2.5
TRA Code	IND-4S

## Load capacity (Kg)

km/h / bar	10.00
10	27000

Printed on 29.04.2024 12:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..