

SM 55 IND-5S - Technische Daten



Description

SM 55 IND-5S wurde speziell für Reach-Stacker und Containerstapler entwickelt. Die spezielle, verschleißfeste Gummimischung gewährleistet ein langes Reifenleben auf Asphaltböden oder Zement und bietet den Maschinen hervorragende Stabilität im Hebemodus.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Containerstapler

Version	PORT SPECIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94039609
Ply Rating	40
Overall Width (inch)	20.4
Overall Diameter (inch)	65.6
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	201.5
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND5

Load capacity (lbs)

mph / psi	145
5	50625

Printed on 23.04.2024 08:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..