

SNOW - RIDE (A) - Technische Daten



Description

SNOW-RIDE ist besonders für Gemeinde- und Wartungsanwendungen in winterlichen Verhältnissen mit Kompaktladern und Skid-Steer-Ladern geeignet. Er zeichnet sich durch hervorragende Traktion aus und ist ideal für den Einsatz auf Schnee und Eis. Das speziell entworfene Laufflächenmuster beseitigt das Risiko von Reifenschlupf und steht für ein langes Reifenleben.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Kompaktlader

Industrie: Skid-Steer-Lader

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions US Standard

Usa code	94044009
Ply Rating	10
Section Width (inch)	10.6
Overall Diameter (inch)	30.7
Static Loaded Radius (inch)	14.1
Rolling Circumference (inch)	92.1
Rim Rec	8.25

Load capacity (lbs)

mph / psi	75
5	4710

Printed on 24.04.2024 10:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..