

SNOW - RIDE (B) - Technische Daten



Description

SNOW-RIDE ist besonders für Straßenanwendungen in winterlichen Verhältnissen mit Ladern und Dozern geeignet. Er zeichnet sich durch ausgezeichnete Traktion aus und ist ideal zum Einsatz auf Schnee und Eis. Das speziell entworfene Laufflächenmuster beseitigt das Risiko von Reifenschlupf.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Planierer • Radlader

Version	STANDARD
Type	TL
Tyre Size	16.9 - 24

Dimensions US Standard

Usa code	94043439
Ply Rating	12
TMPH	1
Section Width (inch)	16.9
Overall Diameter (inch)	51.6
Static Loaded Radius (inch)	23.2
Rolling Circumference (inch)	154.7
Rim Rec	DW 15 L
Rim Alt	DW 14 L

Load capacity (lbs)

mph / psi	38
25	7150

Printed on 26.04.2024 06:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..