

## SNOW RIDE - PLUS - Datenblatt



### Description

SNOW RIDE - PLUS ist besonders für Straßenanwendungen in winterlichen Verhältnissen geeignet. Er zeichnet sich durch ausgezeichnete Traktion aus und ist ideal für den Einsatz auf Schnee und Eis. Das speziell entworfene Laufflächenmuster beseitigt das Risiko von Reifenschlupf.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrie: Radlader

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
20.5 - 25	STANDARD	94058075	L2	16	17.00/2.0	17.00/1.7	20.7	58.5	25.8	172	TL
23.5 - 25	STANDARD	94057740	L2	16	19.50/2.5		23.6	64.2	27.3	187.6	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26.03.2025 14:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..