

## STEER GRIP - Technische Daten



### Description

STEER GRIP ist der perfekte Lenkachsreifen für Kipper. Durch die breite Mittelrippe mit geradlinigen Stollen eignet sich der Reifen besonders für frei rollende Anwendungen und bietet verbesserte Haftung für hervorragende Leistungen bei nassen und trockenen Bedingungen abseits der Straße. Die spezielle Gummimischung der Lauffläche wurde eigens entwickelt, um hervorragende Verschleißfestigkeit mit ausgezeichneter Schnitt- und Reißfestigkeit zu verbinden, während die robuste Karkasse einen verlängerten Produktlebenszyklus gewährleistet.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Kipper

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

## Dimensions International Standard

<b>Ply Rating</b>	20
<b>Overall Width (mm)</b>	310
<b>Overall Diameter (mm)</b>	1248
<b>Static Loaded Radius (mm)</b>	588
<b>Rolling Circumference (mm)</b>	3785
<b>Rim Rec</b>	8.5
<b>Rim Alt</b>	8.0

## Load capacity (Kg)

<b>km/h / bar</b>	<b>7.90</b>
<b>80 LS/LD</b>	<b>3875</b>

Printed on 25.04.2024 07:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..