

## SURE TRAX HD - Technische Daten



### Description

SURE TRAX HD ist ein Reifen mit Blockprofil für Skid-Steer-Lader zum Einsatz im Baugewerbe. Er bietet ausgezeichnete Schnitt- und Reißfestigkeit sowie hervorragenden Felgenschutz. SURE TRAX HD ist ideal für gepflasterte Bodenflächen und schwere Betriebsbedingungen.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Skid-Steer-Lader

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	268
Overall Diameter (mm)	785
Static Loaded Radius (mm)	359
Rolling Circumference (mm)	2316
Rim Rec	8.25
ECE	

## Load capacity (Kg)

	km/h / bar	5.20
	10	2135
	15	1685
	25	1560

Printed on 20.04.2024 05:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..