

## TF 8181 - Technische Daten



### Description

Der TF 8181 Reifen wurde zum Feld- und Straßeneinsatz für 2WD Traktoren zur Bodenbearbeitung und für Transportanwendungen entworfen. Dieser Reifen bietet ein ausgezeichnetes Lenkverhalten.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: 2WD-Traktor  
Industrie: Anhänger

Version	SPECIAL
Type	TT
Tyre Size	6.50 - 16
LI/SS	88 A8

## Dimensions US Standard

Usa code	94045464
Ply Rating	6
Section Width (inch)	7.1
Overall Diameter (inch)	30.3
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	90.4
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5 K ; 5.00 F ; 5.50 F
TRA Code	F2

## Load capacity (lbs)

mph / psi	48
25	1230

Printed on 20.04.2024 17:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..