

## TF 8181 - Technische Daten



### Description

Der TF 8181 Reifen wurde zum Feld- und Straßeneinsatz für 2WD Traktoren zur Bodenbearbeitung und für Transportanwendungen entworfen. Dieser Reifen bietet ein ausgezeichnetes Lenkverhalten.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: 2WD-Traktor  
Industrie: Anhänger

Version	IMPLEMENT
Type	TT
Tyre Size	7.50 - 16
LI/SS	122 A6

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	205
Overall Diameter (mm)	820
Static Loaded Radius (mm)	383
Rolling Circumference (mm)	2445
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
ECE	E4-106R-002670
TRA Code	F2

## Load capacity (Kg)

km/h / bar	5.50
30	1500

Printed on 23.04.2024 16:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..