

TF 9090 - Technische Daten



Description

TF 9090 ist ein Reifen, der für Kleintraktoren zur Bodenbearbeitung entworfen wurde. Das spezielle Laufflächenmuster bietet erstklassiges Lenkverhalten auch auf lockerer Erde.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Kleintraktor
Industrie: Anhänger

Version	STANDARD
Type	TT
Tyre Size	5.50 - 16
LI/SS	82 A8

Dimensions US Standard

Usa code	94020874
Ply Rating	6
Section Width (inch)	5.9
Overall Diameter (inch)	28
Static Loaded Radius (inch)	13.1
Rolling Circumference (inch)	83.3
Rim Rec	4.00 E
Rim Alt	3.50 D ; 4.50 E
ECE	E4-106R-001955
TRA Code	F2

Load capacity (lbs)

mph / psi	56
25	1050

Printed on 11.12.2023 04:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..