

## TF 9090 - Datenblatt



### Description

TF 9090 ist ein Reifen, der für Kleintraktoren zur Bodenbearbeitung entworfen wurde. Das spezielle Laufflächenmuster bietet erstklassiges Lenkverhalten auch auf lockerer Erde.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Kleintraktor  
Industrie: Anhänger

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
4.00 - 12	STANDARD	94033898	F2	56 A8	4	3.00 D	2.50 C	4.4	20.9	10	61.9	TT	E4-106R-002181
4.00 - 12	STANDARD	94035113	F2	60 A8	6	3.00 D	2.50 C	4.4	20.9	10	61.9	TT	E4-106R-002182
5.00 - 15	STANDARD	94020843	F2	69 A8	4	4.00 E	3.00 D ; 4 J ; 4½ J	5.5	25.8	12.1	76.8	TT	E4-106R-001952
5.00 - 15	STANDARD	94020867	F2	76 A8	6	4.00 E	3.00 D ; 4 J ; 4½ J	5.5	25.8	12.1	76.8	TT	
10.00 - 16	SPECIAL	94038831	F2	110 A8	8	W 8	W 8 L	10.8	35.4	16.1	106.9	TT	
10.00 - 16	SPECIAL	94038848	F2	111 A8	10	W 8	W 8 L	10.8	35.4	16.1	106.9	TT	E11-106R-004418
10.00 - 16	STANDARD	94020720	F2	110 A8	8	W 8	W 8 L	10.8	35.4	16.1	106.9	TT	E4-106R-002672
10.00 - 16	STANDARD	94032501	F2	111 A8	10	W 8	W 8 L	10.8	35.4	16.1	106.9	TT	E4-106R-002671
11.00 - 16	SPECIAL	94038572	F2	114 A8	8	W 10 L	W 8 ; W 8 L	12.6	38.2	17.6	113.8	TT	E11-106R-004316
11.00 - 16	STANDARD	94055111	F2	114 A8	8	W 10 L	W 8 ; W 8 L	12.6	38.2	17.6	113.8	TL	E4-106R-002673
11.00 - 16	STANDARD	94020775	F2	114 A8	8	W 10 L	W 8 ; W 8 L	12.6	38.2	17.6	113.8	TT	E4-106R-002673
4.00 - 16	STANDARD	94034680	F2	61 A8	4	3.00 D		4.4	24.8	11.9	73.9	TT	E4-106R-002183
5.50 - 16	STANDARD	94020874	F2	82 A8	6	4.00 E	3.50 D ; 4.50 E	5.9	28	13.1	83.3	TT	E4-106R-001955
6.00 - 16	SPECIAL	94026449	F2	85 A8	6	4.50 E	4.00 E ; 5 K ; 5.00 F	6.7	28.9	13.6	86.2	TT	E11-106R-004410
6.00 - 16	SPECIAL	94032273	F2	91 A8	8	4.50 E	4.00 E ; 5 K ; 5.00 F	6.7	28.9	13.6	86.2	TT	E11-106R-004415
6.00 - 16	STANDARD	94020928	F2	85 A8	6	4.50 E	4.00 E ; 5 K ; 5.00 F	6.7	28.9	13.6	86.2	TT	E4-106R-001959
6.00 - 16	STANDARD	94020959	F2	91 A8	8	4.50 E	4.00 E ; 5 K ; 5.00 F	6.7	28.9	13.6	86.2	TT	E4-106R-001961
6.50 - 16	STANDARD	94021024	F2	88 A8	6	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	7.1	30.1	14.1	89.8	TT	E4-106R-001960
6.50 - 16	STANDARD	94021055	F2	90 A8	8	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	7.1	30.1	14.1	89.8	TT	E4-106R-001962
7.50 - 16	SPECIAL	94026463	F2	94 A8	6	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	31.9	14.9	95	TT	E11-106R-004412
7.50 - 16	SPECIAL	94026470	F2	99 A8	8	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	31.9	14.9	95	TT	E11-106R-004413
7.50 - 16	STANDARD	94021086	F2	94 A8	6	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	31.9	14.9	95	TT	E4-106R-002634
7.50 - 16	STANDARD	94021123	F2	99 A8	8	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	31.9	14.9	95	TT	E4-106R-002709
7.50 - 16	STANDARD	94029952	F2	101 A8	10	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	31.9	14.9	95	TT	E4-106R-002708
9.00 - 16	SPECIAL	94038824	F2	108 A8	10	W 8	6.00 F ; W 7 ; W 8 L	10.1	33.7	15.7	100.3	TT	E11-106R-004114
9.00 - 16	STANDARD	94021307	F2	103 A8	8	W 8	6.00 F ; W 7 ; W 8 L	10.1	33.7	15.7	100.3	TT	E4-106R-002668
9.00 - 16	STANDARD	94021338	F2	108 A8	10	W 8	6.00 F ; W 7 ; W 8 L	10.1	33.7	15.7	100.3	TT	E4-106R-002669
7.50 - 18	SPECIAL	94038589	F2	97 A8	6	5.50 F		8.1	33.9	15.9	100.9	TT	
7.50 - 18	SPECIAL	94038596	F2	102 A8	8	5.50 F		8.1	33.9	15.9	100.9	TT	E11-106R-004318
7.50 - 18	STANDARD	94032600	F2	105 A8	10	5.50 F		8.1	33.9	15.9	100.9	TT	E11-106R-004654
7.50 - 18	STANDARD	94021154	F2	97 A8	6	5.50 F		8.1	33.9	15.9	100.9	TT	E11-106R-004317
7.50 - 18	STANDARD	94021192	F2	102 A8	8	5.50 F		8.1	33.9	15.9	100.9	TT	E4-106R-002645
4.00 - 19	STANDARD	94020805	F2	69 A8	4	3.00 D		4.5	28.1	13.5	84.4	TT	E11-106R-003355

6.00 - 19	STANDARD	94020973	F2	89 A8	6	4.50 E	4.00 E ; 5.00 F	6.6	32.1	15.2	96.3	TT	E11-106R-003472
7.50 - 20	SPECIAL	94038800	F2	99 A8	6	5.50 F	5.00 F	8.1	36	17	107.3	TT	
7.50 - 20	SPECIAL	94038817	F2	105 A8	8	5.50 F	5.00 F	8.1	36	17	107.3	TT	
7.50 - 20	STANDARD	94021222	F2	99 A8	6	5.50 F	5.00 F	8.1	36	17	107.3	TT	E4-106R-002635
7.50 - 20	STANDARD	94021260	F2	105 A8	8	5.50 F	5.00 F	8.1	36	17	107.3	TT	E4-106R-002710

Printed on 10.12.2023 18:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..