

## TF 9393 - Technische Daten



### Description

TF 9393 ist ein Landwirtschaftsreifen für die Vorderachse, der speziell für kompakte Traktoren zur Bodenbearbeitung und speziell zum Einsatz auf lockerer Erde entwickelt wurde. Das Profil weist einen breiten Mittelteil und Schulterrippen auf. Das spezielle Laufflächenmuster verleiht hervorragende Lenkbarkeit auf allen Oberflächen.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Kleintraktor

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

## Dimensions US Standard

Usa code	94046263
Ply Rating	8
Section Width (inch)	8.3
Overall Diameter (inch)	31.9
Rim Rec	5.50 F
Rim Alt	5.00 F ; 6.00 F
TRA Code	F2

## Load capacity (lbs)

mph / psi	56
25	1545

Printed on 23.04.2024 12:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..