

TR 118 - Technische Daten



Description

TR 118 ist speziell für Beregnungsmaschinen konzipiert. TR 118 zeichnet sich durch eine verstärkte Karkasse und eine höhere Anzahl an Stollen aus, wodurch eine längere Betriebsdauer gewährleistet ist.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Pivot-Beregnungsmaschine

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	128 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	380
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	566
Rolling Circumference (mm)	3742
SRI (mm)	600
Rim Rec	W 13
Rim Alt	W 12 ; W 11
ECE	E11-106R-004420
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.80	2.35
30	1800	---
CREEP	---	3375

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN)

Printed on 24.04.2024 08:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..