

## TR 126 - Technische Daten



### Description

TR 126 wurde für kleine Traktoren zur Bodenbearbeitung entworfen. Tiefe Stollen und ein tiefes Laufflächenprofil bieten ausgezeichnete Traktion und erstklassige Tragfähigkeit. Der Reifen zeichnet sich durch hervorragende Leistung bei allen Einsatzbedingungen aus.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Kleintraktor

Version	HD
Type	TT
Tyre Size	6 - 14
LI/SS	80 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	157
Overall Diameter (mm)	655
Static Loaded Radius (mm)	305
Rolling Circumference (mm)	1978
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-007418
TRA Code	R1

## Load capacity (Kg)

km/h / bar	3.85
30	450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08.12.2024 16:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..