

TR 135 - Technische Daten



Description

TR 135 eignet sich bestens zur Bodenbearbeitung mit Traktoren. Die verstärkte Karkasse und die spezielle, schnitt- und stichfeste Gummimischung stehen für ein verlängertes Reifenleben. Traktion, Selbstreinigungseigenschaften und Tragfähigkeit sind Schlüsseleigenschaften, die den TR 135 Reifen zum idealen Partner auch auf schwierigen Bodenverhältnissen machen.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

Industrie: Anhänger

Version	STANDARD
Type	TT
Tyre Size	14.9 - 30
LI/SS	127 A8

Dimensions US Standard

Usa code	94029372
Ply Rating	8
Section Width (inch)	14.9
Overall Diameter (inch)	55.7
Static Loaded Radius (inch)	25.9
Rolling Circumference (inch)	169.9
Rim Rec	W 13
Rim Alt	W 11 ; W 12
ECE	E4-106R-002753
TRA Code	R1

Load capacity (lbs)

mph / psi	26
25	3860

Printed on 23.04.2024 16:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..