

TR 135 - Technische Daten



Description

TR 135 eignet sich bestens zur Bodenbearbeitung mit Traktoren. Die verstärkte Karkasse und die spezielle, schnitt- und stichfeste Gummimischung stehen für ein verlängertes Reifenleben. Traktion, Selbstreinigungseigenschaften und Tragfähigkeit sind Schlüsseleigenschaften, die den TR 135 Reifen zum idealen Partner auch auf schwierigen Bodenverhältnissen machen.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor
Industrie: Anhänger

Version	HD
Type	TT
Tyre Size	16.9 - 34
LI/SS	142 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	429
Overall Diameter (mm)	1585
Static Loaded Radius (mm)	728
Rolling Circumference (mm)	4794
SRI (mm)	750
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-004440
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.00
30	2650

Printed on 23.04.2024 10:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..