

TR 136 - Technische Daten



Description

TR 136 wurde von BKT zur Ausstattung von Traktoren und Anhängern bei der Bodenbearbeitung und Transportarbeiten entwickelt. Dieser Reifen verleiht verbesserte Traktion bei jeglichen Einsatzbedingungen neben hervorragender Schnitt- und Reißfestigkeit. Dies reduziert Stillstandzeiten und steigert Ihre Produktivität. Dank der erhöhten Anzahl an Stollen bietet TR 136 erstklassige Traktion auch bei hohen Lasten.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor • Anhänger

Version	STANDARD
Type	TT
Tyre Size	18.4 - 30
LI/SS	135 A8

Dimensions US Standard

Usa code	94027514
Ply Rating	8
Section Width (inch)	18.4
Overall Diameter (inch)	61
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	185.8
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-004473
TRA Code	R1

Load capacity (lbs)

	mph / psi	20
	25	4800

Printed on 28.11.2023 14:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..