

TR 136 - Datenblatt



Description

TR 136 wurde von BKT zur Ausstattung von Traktoren und Anhängern bei der Bodenbearbeitung und Transportarbeiten entwickelt. Dieser Reifen verleiht verbesserte Traktion bei jeglichen Einsatzbedingungen neben hervorragender Schnitt- und Reißfestigkeit. Dies reduziert Stillstandzeiten und steigert Ihre Produktivität. Dank der erhöhten Anzahl an Stollen bietet TR 136 erstklassige Traktion auch bei hohen Lasten.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor • Anhänger

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|------------------------|----------|----------|--------|----|---------|------------|-----|------|-----|------|-----|------|-----------------|
| 18.4 - 26 | SPECIAL | R1 | 146 A6 | 12 | W 16 L | W 15 L | 480 | 1450 | 646 | 4205 | 675 | TL | E11-106R-003614 |
| 18.4 - 26 | STANDARD | R1 | 150 A6 | 14 | W 16 L | W 15 L | 480 | 1450 | 646 | 4205 | 675 | TL | E4-106R-002301 |
| 18.4 - 26 | STANDARD | R1 | 146 A6 | 12 | W 16 L | W 15 L | 480 | 1450 | 646 | 4205 | 675 | TL | |
| 18.4 - 26 | STANDARD | R1 | 146 A6 | 12 | W 16 L | W 15 L | 480 | 1450 | 646 | 4205 | 675 | TT | E4-106R-002718 |
| 12.4 - 28 | STANDARD | R1 | 123 A6 | 8 | W 11 | W 9 ; W 10 | 315 | 1275 | 595 | 3749 | 600 | TT | E11-106R-003551 |
| 16.9 - 30 | HD | R1 | 137 A6 | 8 | W 15 L | W 14 L | 429 | 1485 | 677 | 4455 | 700 | TT | E11-106R-004470 |
| 16.9 - 30 | SPECIAL | R1 | 143 A6 | 12 | W 15 L | W 14 L | 429 | 1485 | 687 | 4523 | 700 | TL | |
| 16.9 - 30 | SPECIAL | R1 | 137 A6 | 8 | W 15 L | W 14 L | 429 | 1485 | 677 | 4455 | 700 | TT | E11-106R-004470 |
| 16.9 - 30 | SPECIAL | R1 | 143 A6 | 12 | W 15 L | W 14 L | 429 | 1485 | 687 | 4523 | 700 | TT | E11-106R-003010 |
| 16.9 - 30 (14 - 30) | STANDARD | R1 | 146 A6 | 14 | W 15 L | W 14 L | 429 | 1485 | 677 | 4455 | 700 | TT | E11-106R-005243 |
| 16.9 - 30 | STANDARD | R1 | 137 A6 | 8 | W 15 L | W 14 L | 429 | 1485 | 677 | 4455 | 700 | TT | E11-106R-003441 |
| 16.9 - 30 | STANDARD | R1 | 139 A6 | 10 | W 15 L | W 14 L | 429 | 1485 | 677 | 4455 | 700 | TT | E11-106R-004472 |
| 16.9 - 30 | STANDARD | R1 | 143 A6 | 12 | W 15 L | W 14 L | 429 | 1485 | 687 | 4523 | 700 | TT | |
| 18.4 - 30 | HD | R1 | 139 A6 | 8 | W 16 L | W 15 L | 467 | 1550 | 712 | 4719 | 725 | TT | E11-106R-004435 |
| 18.4 - 30 | HD | R1 | 149 A6 | 12 | W 16 L | W 15 L | 467 | 1550 | 712 | 4719 | 725 | TT | E11-106R-004475 |
| 18.4 - 30 | HD | R1 | 151 A6 | 14 | W 16 L | W 15 L | 467 | 1550 | 712 | 4719 | 725 | TT | E11-106R-003615 |
| 18.4 - 30 | SPECIAL | R1 | 149 A6 | 12 | W 16 L | W 15 L | 467 | 1550 | 712 | 4719 | 725 | TT | E11-106R-004436 |
| 18.4 - 30 | STANDARD | R1 | 139 A6 | 8 | W 16 L | W 15 L | 467 | 1550 | 712 | 4719 | 725 | TT | E11-106R-004473 |

Printed on 11.12.2023 23:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..